

10-AU Field Fluorometer



Highlights of the 10AU

- Exceptional Sensitivity
- Automatic or Manual Ranging
- Analog and Digital Output
- Field Installable Optical Kits
- Easy to Read LCD Display

10AU Field Fluorometer

The 10AU Field Fluorometer is a rugged, field-portable instrument that can be set up for continuous-flow monitoring or discrete sample analyses. Measurements are extremely stable with stability measured in months or weeks as opposed to days or hours. Watertight filter paddles enable quick change of excitation and emission filters so a variety of compounds can be easily measured on-site.

Available Optical Kits

Optical kits with appropriate filters and lamps are available for a wide range of applications and can be easily installed in the field or lab. Individual filters and lamps can also be purchased for customized applications.

Available Optical Kits

- Chlorophyll *a* - Extracted and/or *In Vivo*
- Blue Green Algae - Phycocyanin (freshwater)
- Blue Green Algae - Phycoerythrin (marine)
- Rhodamine WT Dye Tracing
- Fluorescein Dye Tracing
- Ammonium
- CDOM
- Crude Oil (Long Wavelength)
- Refined Oil (Short Wavelength)
- Histamine
- Optical Brighteners

Contact Us for Custom Optical Kits

User Configured Options

- Indoor or Watertight housing
- Standard or Red PMT
- Continuous Flow Monitoring or Discrete Sample Analysis



Optional Accessories

- Internal Data Logging & Electronic Chart Recording
- Temperature Compensation for Continuous Flow Measurements
- Solid Secondary Standard

Reliable Instruments for an Unreliable World

10-AU Field Fluorometer



Ordering Information

BASE INSTRUMENT	PART NUMBER
10AU Fluorometer with Red PMT	10AU-072
10AU Fluorometer with Standard PMT	10AU-073

INSTRUMENT HOUSING	PART NUMBER
Indoor Case	10-AU-002
Watertight Case	10-AU-022

SAMPLE CELL	PART NUMBER
25mm One-Piece Continuous Flow System	10-AU-020
25 mm & 13 mm Discrete Sample Test Tube Holder Set	10-AU-030

SOFTWARE	PART NUMBER
Internal Data Logging & Electronic Chart Recording	10-AU-450
Temperature Compensation Package (On-Line Systems)	10-AU-500

OPTICAL KITS	PART NUMBER
<i>In Vivo</i> & Extractive Chlorophyll <i>a</i>	10-037R
Extractive Chlorophyll <i>a</i>	10-040R
<i>In Vivo</i> Chlorophyll <i>a</i>	10-096R
Blue Green Algae - Phycocyanin (freshwater)	10-305
Blue Green Algae - Phycoerythrin (marine)	10-304
Rhodamine WT Dye	10-041R
Fluorescein Dye	10-086R
Ammonium/CDOM	10-303
Crude Oil (Long Wavelength Oil)	10-302R
Refined Oil (Short Wavelength Oil)	10-301R
Optical Brighteners	10-302R

Contact Us for Custom Optical Kits

OPTIONAL ACCESSORIES	PART NUMBER
Solid Secondary Standard	10-AU-904
Shipping Case	10-AU-060
12 VDC Power & Signal Cable w/ Clips	10-AU-012C
Universal Power & Signal Cable, 115 VAC & 230 VAC	10-AU-1155

Contact Us

Toll-Free : 1.877.316.8049

Phone : 408.749.0994

Fax : 408.749.0998

Email : sales@turnerdesigns.com

Web : www.turnerdesigns.com

Address:

845 West Maude Avenue

Sunnyvale, CA 94085

10AU Electrical Specifications

Light Source	Lamp (4 watts, 8000 hours lamp life)
Detector	PhotoMultiplier Tube; Standard (300-650 nm), Red (185-870 nm)
AC Power	100-130 V; 200-240 V, 50/60 Hz, 30 watts
DC Power	11-16 V; 2.5 amperes
Digital Output	100% ASCII data output via RS-232 at 4800 or 9600 bps
Analog Output	0.1, 1, 2, or 5 volts

10AU Detection Limits

Extracted Chlorophyll <i>a</i>	0.025 µg/L using EPA Method 445.0
Rhodamine WT Dye	0.01 ppb RWT in potable water
Fluorescein Dye	0.01 ppb Fluorescein in potable water

10AU Linear Range

Extracted Chlorophyll <i>a</i>	0 - 250 µg/L
Rhodamine WT Dye	0 - 250 ppb
Fluorescein Dye	0 - 250 ppb

10AU Physical Specifications

Weight	15.6 Kg (34.5 lbs)
Height	24 cm (9.45 in)
Width	55 cm (21.65 in)
Depth	34 cm (13.39 in)
Operating Temperature	0-55° C, 32-131° F (ambient)